

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/09/2014

Revised On 10/09/2014

1 Identification of the substance and manufacturer

Trade name: RED FLUORESCENT UPRIGHT

Product code: 0000201754

Product category: PC9a Paints and coatings.

Manufacturer/Supplier: Seymour of Sycamore
917 Crosby Avenue
Sycamore, IL 60178
Phone: 815-895-9101 www.seymourpaint.com

Emergency telephone number: CHEMTEL 1-800-255-3924, 813-248-0585 *if located outside the U.S.*



2 Hazard(s) identification

Classification of the substance or mixture

Flam. Aerosol 1 H222 Extremely flammable aerosol.
 Press. Gas H280 Contains gas under pressure; may explode if heated.
 Carc. 2 H351 Suspected of causing cancer.
 STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.
 Eye Irrit. 2A H319 Causes serious eye irritation.

GHS Hazard pictograms



GHS02 GHS04 GHS07 GHS08

Signal word Hazard statements

Danger
 Extremely flammable aerosol.
 Contains gas under pressure; may explode if heated.
 Causes serious eye irritation.
 Suspected of causing cancer.

Precautionary statements

May cause damage to organs through prolonged or repeated exposure.
 If medical advice is needed, have product container or label at hand.
 Keep out of reach of children.
 Read label before use.
 Obtain special instructions before use.
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 Do not spray on an open flame or other ignition source.
 Pressurized container: Do not pierce or burn, even after use.
 Wash hands thoroughly after handling.
 Wear protective gloves/protective clothing/eye protection/face protection.
 Do not handle until all safety precautions have been read and understood.
 Do not breathe dust/fume/gas/mist/vapors/spray.
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 Get medical advice/attention if you feel unwell.
 IF exposed or concerned: Get medical advice/attention.
 If eye irritation persists: Get medical advice/attention.
 Store locked up.
 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
 Store in a well-ventilated place.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:

64742-89-8	VM&P Naphtha	18.33%
74-98-6	propane	15.13%
1317-65-3	Calcium Carbonate	11.43%
106-97-8	n-butane	8.88%
64742-47-8	Mineral Spirits	3.8%
110-19-0	isobutyl acetate	3.21%

4 First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.
After skin contact: Remove contaminated clothing. Wash exposed area with soap and water.
After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
After swallowing: Rinse out mouth and then drink plenty of water.
 Rinse mouth with water. Do not induce vomiting.

Most important symptoms and effects:

Dizziness

Indication of any immediate medical attention needed:

No further relevant information available.

5 Fire-fighting measures

Extinguishing agents: CO₂, extinguishing powder or water spray. Fight larger fires with water spray.
Special hazards: Can form explosive gas-air mixtures.

(Contd. on page 2)
US4

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/09/2014

Revised On 10/09/2014

Trade name: RED FLUORESCENT UPRIGHT

(Contd. of page 1)

Protective equipment for firefighters:

A respiratory protective device may be necessary.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures:

 Wear protective equipment. Keep unprotected persons away.
 Use respiratory protective device against the effects of fumes/dust/aerosol.

Methods and material for containment and cleaning up:

Ensure adequate ventilation.

7 Handling and storage

**Precautions for safe handling
Storage requirements:**

 Use only in well ventilated areas.
 Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.

8 Exposure controls/personal protection

Components with limit values that require monitoring at the workplace:

74-98-6 propane

 PEL (USA) Long-term value: 1800 mg/m³, 1000 ppm

 REL (USA) Long-term value: 1800 mg/m³, 1000 ppm

TLV (USA) refer to Appendix F

106-97-8 n-butane

 REL (USA) Long-term value: 1900 mg/m³, 800 ppm

 TLV (USA) Short-term value: 2370 mg/m³, 1000 ppm

110-19-0 isobutyl acetate

 PEL (USA) Long-term value: 700 mg/m³, 150 ppm

 REL (USA) Long-term value: 700 mg/m³, 150 ppm

 TLV (USA) Long-term value: 713 mg/m³, 150 ppm

Hygienic protection:

Keep away from foodstuffs and animal feed. Wash hands after use.

Wash hands after use.

Do not eat or drink while working.

Breathing equipment:

 A respirator is generally not necessary when using this product outdoors or in large open areas.
 In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.

Hand protection:

Protective gloves. The glove material must be impermeable and resistant to the substance.

Eye protection:

Tightly sealed goggles

9 Physical and chemical properties

Appearance:

Aerosol.

Odor:

Pleasant

Odor threshold:

Not determined.

pH-value:

Not determined.

Melting point/Melting range

Undetermined.

Boiling point:

-44 °C (-47 °F)

Flash point:

-19 °C (-2 °F)

Flammability (solid, gas):

Extremely flammable.

Decomposition temperature:

Not determined.

Auto igniting:

Product is not self-igniting.

Danger of explosion:

In use, may form flammable/explosive vapour-air mixture.

Lower Explosion Limit:

1.7 Vol %

Upper Explosion Limit:

10.9 Vol %

Vapor pressure:

Not determined.

Relative Density:

Between 0.77 and 0.85 (Water equals 1.00)

Vapour density

Not determined.

Evaporation rate

Not applicable.

Partition coefficient: n-octanol/water:

Not determined.

Solubility:

Not determined.

Viscosity:

Not determined.

VOC content:

524.7 g/l / 4.38 lb/gl

VOC content (less exempt solvents):

50.5 %

Water:

24.4 %

MIR Value:

0.58

Solids content:

24.1 %

10 Stability and reactivity

Reactivity:

Stable at normal temperatures.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 10/09/2014

Revised On 10/09/2014

Trade name: RED FLUORESCENT UPRIGHT

(Contd. of page 2)

Conditions to avoid: Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures.

Chemical stability: Not fully evaluated.

Possibility of hazardous reactions: No dangerous reactions known.

Incompatible materials: No further relevant information available.

Hazardous decomposition: No dangerous decomposition products known.

11 Toxicological information

LD/LC50 values that are relevant for classification:

106-97-8 n-butane

Inhalative LC50/4 h 658 mg/l (rat)

110-19-0 isobutyl acetate

Oral LD50 4763 mg/kg (rbt)

Information on toxicological effects: No data available.

Sensitization: No sensitizing effects known.

Carcinogenic categories

IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

NTP (National Toxicology Program)

None of the ingredients is listed.

OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

Aquatic toxicity: Hazardous for water, do not empty into drains.

Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes.

Bioaccumulative potential: No further relevant information available.

Mobility in soil: No further relevant information available.

Other adverse effects: No further relevant information available.

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Completely empty cans should be recycled.

14 Transport information

UN-Number UN1950

DOT Aerosols, flammable

ADR 1950 Aerosols

Transport hazard class(es):

Class 2.1

Marine pollutant: No

Special precautions for user: Warning: Gases

EMS Number: F-D,S-U

Packaging Group: --

UN "Model Regulation": UN1950, Aerosols, 2.1

15 Regulatory information

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

CPSC: This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

100-41-4 ethyl benzene

EPA:

110-19-0 isobutyl acetate

D

16 Other information

Contact: Regulatory Affairs

US4